

Billerud Pure Decor™ LINER

Product Description

The light coated Pure Decor™ kraftliner is a preferred material for high quality post-print and pre-print. High strength ensures light, strong packages with minimised washboarding. Pure Decor™ is produced from 100% virgin fibres.

Grammages

120, 145, 160, 175 g/m²

Approvals

Pure Decor™ is produced in compliance with FDA and BfR packaging norms.

Certification

Production is certified in accordance with ISO 9001, ISO 14001, ISO 50001 and FSSC 22000.

Property	Unit						Method
Grammage	g/m ²		120	145	160	175	ISO 536
Caliper	µm		145	180	195	210	ISO 534
Scott Bond	J/m ²		350	350	350	350	TAPPI T569
Burst strenght	kPa		560	700	770	840	ISO 2759
SCT	CD	kN/m	2,8	3,2	3,6	4,0	ISO 9895
Tensile Stiffness	MD	kN/m	1000	1200	1300	1400	ISO 1924
	CD	kN/m	500	600	700	800	
Roughness PPS-10	PS	µm	1,4	1,5	1,6	1,7	ISO 8791-4
Gloss	PS	%	42	42	42	42	TAPPI T480
Brightness	PS	%	80	80	80	80	ISO 2470
Whiteness D65	PS	%	80	81	81	81	ISO 11475
Cobb	PS	g/m ²	34	34	34	34	ISO 535
	RS	g/m ²	38	38	38	38	
Moisture	%		7,0	7,0	7,0	7,0	ISO 287

MD = Machine Direction CD = Cross Direction PS = Print Side RS = Reverse Side Test climate: 50% RH, 23°C

The table shows typical data for a range of grammages.

Rev. 202502