

Billerud Pure White LINER

Product Description

Pure White is a fully white kraftliner produced from 100% virgin fibres. The characteristics for this grade are high and consistent quality combined with superior runnability.

Grammages

80, 110, 120, 135 g/m²

Approvals

Pure White is produced in compliance with FDA and BfR packaging norms.

Certification

Production is certified in accordance with ISO 9001, ISO 14001, ISO 50001 and FSSC 22000.

Property	Unit						Method
Grammage	g/m ²		80	110	120	135	ISO 536
Caliper	µm		95	130	145	165	ISO 534
Air resistance	s		60	60	60	60	ISO 5636-5
Scott Bond	J/m ²		400	350	350	350	TAPPI T569
Burst strenght	kPa		360	510	560	630	ISO 2758
SCT	CD	kN/m	1,6	2,2	2,4	2,8	ISO 9895
Tensile Stiffness	MD	kN/m	800	1060	1140	1260	ISO 1924
	CD	kN/m	340	450	480	550	
Roughness	PS	ml/min	190	260	300	350	ISO 8791-2
Brightness	%		81	81	81	81	ISO 2470
Whiteness			75	75	75	75	ISO 11475
Cobb	PS	g/m ²	23	23	23	23	ISO 535
	RS	g/m ²	35	35	35	35	
Moisture	%		7,5	7,5	7,5	7,5	ISO 287

MD = Machine Direction CD = Cross Direction PS = Print Side RS = Reverse Side Test climate: 50% RH, 23°C

The table shows typical data for a range of grammages.

Rev. 202602